

TECHNICAL DATA

COMPOSITE TAPE

Product Code: 1H861

P. Leo & Co (B. C.) Ltd.

150-12820 Clarke Place, Richmond, B.C. V6V 2H1, Canada

Telephone : (604)270-6115 * Facsimile : (604)538-2909 * E-mail : sales@pleo.com

Web Site : <http://www.pleo.com>



UL FILE #E126174

Description: 1H861 is polyester film reinforced/laminated with polyester non-woven coated with Arcylic adhesive. High adhesion strength, tear and oil resistance.

Application: Ideal for insulating, banding, anchoring, holding in motors and transformers. It is used in transformer as margin tape between coil and transformer body.

Technical Details:

<u>PROPERTIES</u>	<u>UNITS</u>	<u>SPECIFICATION</u>
COLOR	-	Natural
TOTAL THICKNESS	mm	0.17±0.01
TENSILE STRENGTH	kg/25mm	13.33
ELONGATION	%	70
ADHESION TO STEEL	kg/25mm	1.20
DIELECTRIC BREAKDOWN	kV	4
TEMPERATURE CLASS	°C	130

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.