

# TECHNICAL DATA

## POLYIMIDE FILM TAPE

**Product Code: 1K7177**

*P. Leo & Co (B. C.) Ltd.*

150-12820 Clarke Place, Richmond, B.C. V6V 2H1, Canada

Telephone : (604)270-6115 \* Facsimile : (604)538-2909 \* E-mail : sales@pleo.com

Web Site : <http://www.pleo.com>



UL FILE #E126174

Description: 1 mil polyimide film tape with acrylic based thermosetting pressure sensitive adhesive.

Features/Benefits: This product features toughness, puncture resistance, conformability and Class 150°C performance for electrical application.

Technical Details:

<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
COLOR	-	amber
TOTAL THICKNESS	mm	0.063
BACKING THICKNESS	mm	0.025
TENSILE STRENGTH	kg/25mm	13.636
ELONGATION AT BREAK	%	50
ADHESIVE TO STEEL	kg/25mm	1.136
BREAKDOWN VOLTAGE	kV	7.0
TEMPERATURE CLASS	°C	150

Availability: Standard 33M roll, 3" core, width 600mm

### **Important Notice to Purchase**

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or \*he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.