

TECHNICAL DATA

POLYIMIDE FILM TAPE

Product Code: 1K7270

P. Leo & Co (B. C.) Ltd.

150-12820 Clarke Place, Richmond, B.C. V6V 2H1, Canada

Telephone : (604)270-6115 * Facsimile : (604)538-2909 * E-mail : sales@pleo.com

Web Site : <http://www.pleo.com>



UL FILE #E126174

- Description: 2 mil (1K7270) polyimide film tape with silicone adhesive.
- Application: High temperature (180°C) performance in masking and DC/ fractional motor applications.
- Features/Benefits: High puncture resistance, conformable, good high temperature performance.

Technical Details:

<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
COLOR	-	amber
TOTAL THICKNESS	mm	0.0875
BACKING THICKNESS	mm	0.05
TENSILE STRENGTH	kg/25mm	29.545
ELONGATION AT BREAK	%	60
ADHESION TO STEEL	kg/25mm	0.568
BREAKDOWN VOLTAGE	kV	8.5
TEMPERATURE CLASS	°C	180

Availability: Standard 33M roll, 3" core, width 600mm

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.