

TECHNICAL DATA

POLYIMIDE FILM TAPE

Product Code: 1KPST

P. Leo & Co (B. C.) Ltd.

150-12820 Clarke Place, Richmond, B.C. V6V 2H1, Canada

Telephone : (604)270-6115 * Facsimile : (604)605-6128

E-mail : sales@pleo.com

Web Site : <http://www.pleo.com>



UL FILE #E126174

Description: 1KPST made by 1 mil polyimide film tape with acrylic based thermosetting pressure sensitive adhesive.

Features/Benefits: For use in high performance electrical applications, used on high-temperature coils, such as in traction machine manufacturing, in the production of generators and transformers etc. This product features toughness, puncture resistance, conformability and performance for Class F to Class N electrical insulation application.

Technical Details:

<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
COLOR	-	amber
TOTAL THICKNESS	mm	0.06
BACKING THICKNESS	mm	0.025
TENSILE STRENGTH	kg/25mm	12
ELONGATION AT BREAK	%	50
ADHESIVE TO STEEL	kg/25mm	0.7
BREAKDOWN VOLTAGE	kV	7.0
TEMPERATURE RATING	°C	155

Availability: Standard 33M roll, 3" core, width 600mm

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection therewith.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.